



## Afstandsbediening / Remote Control



## Eigenschappen

- » Alleen geschikt voor de DELTA® kettingtakel model US en de DELTA® lieren model DKL en DPS.
- » Kan achteraf worden gemonteerd en afwisselend worden gebruikt met de stuurkabel.
- » Lichte, maar robuuste zender uitgerust met noodstop.
- » Afmetingen zender (LxBxH): 190 x 70 x 50
- » Afmetingen ontvanger (LxBxH): 175 x 125 x 75
- » Voldoet aan de Machinerichtlijn 2006/42/EG.

## Features

- » Only suitable for the DELTA® chain hoist model US and the DELTA® winches model DKL and DPS.
- » Can be retrofitted and used alternately with the control cable through plug&play connection.
- » Light, yet robust transmitter equipped with emergency stop button.
- » Dimensions transmitter (LxWxH): 190 x 70 x 50
- » Dimensions receiver (LxWxH): 175 x 125 x 75
- » Complies with the Machinery Directive 2006/42/EC.

Eenvoudige plug&play-aansluiting /  
Easy plug&play connection

Specificaties / Specifications		
Zender		Ontvanger
Transmitter		Receiving Unit
Besturing bescherming / Control protection		IP 65
Operatiebereik vrije ruimte / Operation distance in open space		100 m
Bedrijfstemperatuur / Operating temperature		-10°C - +40°C
Netto gewicht / Net weight	0.4 kg	1.9 kg
Stroomvoorziening / Power supply	6V (4x AA)	-

Specificaties / Specifications	
Artikel nummer	Type
Article code	Model
CZ.RC.US.901.902	CZ.0.US.901
	CZ.0.US.902
	CZ.0.US.903
	CZ.0.US.904
CZ.RC.US.903.904	CP.0.DKL.160
	CP.0.DKL.230
	CP.0.DKL.300
	CP.0.DKL.500
CZ.RC.DKL	CP.0.DPS.200
	CP.0.DPS.250
	CP.0.DPS.300
	CP.0.DPS.500
CZ.RC.DPS	CP.0.DPS.200
	CP.0.DPS.250
	CP.0.DPS.300
	CP.0.DPS.500